

XRAY XB9

FRONT

STEERING BLOCK

PLASTIC ☐

ALU ☐

KING PIN 5° ☐

CASTER BLOCK

PLASTIC ☐

ALU ☐

OFFSET

STANDARD ☐

+1 ☐

+2 ☐

FRONT DROOP

MEASURE UNDER WHEEL AXLE

UPPER SHOCK POSITION

FRONT ROLL CENTER

REAR ROLL CENTER

CAMBER LINK LOCATION

REAR LOWER SHOCK POSITION

HUB POSITION

REAR

SHIM /mm

OFFSET

STANDARD ☐

+1 ☐

+2 ☐

UPRIGHT

PLASTIC ☐

ALU ☐

REAR DROOP

MEASURE UNDER WHEEL AXLE

FRONT

CASTER

10° ☐

12° ☐

14° ☐

UPPER PLATE-RADIO PLATE STIFFENER

YES ☐ NO ☐

WHEELBASE SHIM POSITION

0mm ☐ 2mm ☐ 2+2mm ☐

SHIMS BEHIND FRONT ARM

REAR

WHEELBASE SHIM POSITION

0mm ☐ 2mm ☐ 2+2mm ☐

SHIMS IN FRONT OF REAR ARM

ROLL CENTER ECCENTRIC BUSHINGS

FF

1 ☐ 0.5 ☐

FR

1 ☐ 0.5 ☐

RF

1 ☐ 0.5 ☐

RR

1 ☐ 0.5 ☐

FRONT TOE

OUT

SERVO SAVER

TIGHT ☐

MEDIUM ☐

SOFT ☐

BUMP STEER

mm

SHIM UNDER STEERING PLATE

REAR TOE

IN

WHEELBASE

0mm ☐ 1mm ☐ 2mm ☐ 3mm ☐ 4mm ☐

SHIMS IN FRONT OF UPRIGHT

ANTI-ROLL BAR POSITION

FRONT

FRONT CAMBER

+

-

SHOCK PRELOAD

mm

FRONT ARM

STANDARD ☐

F. RIDE HEIGHT

mm

REAR

REAR CAMBER

-

+

SHOCK PRELOAD

mm

REAR ARM

STANDARD ☐

R. RIDE HEIGHT

mm

FRONT

CHASSIS FLEX SETTINGS

SCREW USED ☒

SCREW NOT USED ☐

FRONT WEIGHT

kg

WING

STANDARD ☐