

# SET-UP SHEET

# XRAY RX8

RACE	BASIC SET-UP		
TRACK			
NAME			
CITY / COUNTRY			
CONTACT			

DATE		TEMPERATURE / °F or °C	AIR	TRACK
QUALIFYING POSITION	BEST LAPTIME / sec	FINAL POSITION	LAPS	RACE LENGTH / minutes
TRACK CONDITION		<input type="checkbox"/> SMOOTH <input type="checkbox"/> TECHNICAL <input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> MIXED <input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY <input type="checkbox"/> FAST <input type="checkbox"/> HIGH
TRACTION				

GEARING														
PINION	1ST	16	17	<input checked="" type="checkbox"/>	18		SPUR	1ST	48	49	<input checked="" type="checkbox"/>	50		
	2ND	19	20	<input checked="" type="checkbox"/>	21			2ND	45	46	<input checked="" type="checkbox"/>	47		
PULLEY		28	29	<input checked="" type="checkbox"/>			RATIO 1ST		6.92		RATIO 2ND		5.52	

FRONT	SHOCKS	REAR
KIT	SPRING	KIT
600	OIL / cSt	600
25%	REBOUND %	25%
Standard	MEMBRANE	Standard
<input checked="" type="checkbox"/> YES <input type="checkbox"/> PLASTIC <input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO <input checked="" type="checkbox"/> ALU <input type="checkbox"/> NO	<input checked="" type="checkbox"/> YES <input type="checkbox"/> PLASTIC <input checked="" type="checkbox"/> YES
FOAM INSERTS		
SHOCK BODY		
ADJUSTABLE PISTONS		
HOLE IN PISTON /mm		

<input type="radio"/> OPENED <input checked="" type="radio"/> CLOSED		HOLES IN PISTON	
---	--	-----------------	--

FRONT	ANTI-ROLL BAR	REAR
<input checked="" type="checkbox"/> 0° <input type="checkbox"/> 30° <input type="checkbox"/> 45° <input type="checkbox"/> 60° <input type="checkbox"/> 90°	<input type="checkbox"/> 0° <input type="checkbox"/> 30° <input type="checkbox"/> 45° <input type="checkbox"/> 60° <input type="checkbox"/> 90°	<input type="checkbox"/> 0° <input type="checkbox"/> 30° <input type="checkbox"/> 45° <input type="checkbox"/> 60° <input type="checkbox"/> 90°
WIRE		KIT
/mm		0

FRONT	TIRES	REAR
LEFT	RIGHT	LEFT
	MANUFACTURER	
	SHORE / deg°	
	DIAMETER / mm	
	5 MIN. WEAR /mm	
	RUBBER TIRES	

ENGINE			
TYPE			
CARB. DIA /mm	HEAD SHIM /mm	PLUG	
MUFFLER	FUEL		

CLUTCH / BRAKE			
FLYWHEEL	<input checked="" type="checkbox"/> STANDARD	OTHER	
CLUTCH FLYWEIGHTS	<input checked="" type="checkbox"/> STANDARD	OTHER	
CLUTCH SHOE	RED	CLUTCH SPRING	<input checked="" type="checkbox"/> STANDARD
CLEARANCE /mm	0.7	ADJ. NUT /mm	
BRAKE PAD	<input checked="" type="checkbox"/> STANDARD	OTHER	
BRAKE SETTING %			

BODY	
WING HEIGHT	
WING POSITION	

COMMENTS	
----------	--

FRONT	REAR
ECCENTER POSITION SHIM/mm 0	ECCENTER POSITION SHIM/mm 0
WHEELBASE/mm	293
8	9
RIDE HEIGHT/mm	
AUTOMATICALLY CALCULATED	

FRONT	REAR
STEERING BLOCK STANDARD <input checked="" type="checkbox"/> OTHER SHIM/mm 1.5	ROLL CENTER SHIM/mm 1.5
UPSTOP	UPPER SHOCK POSITION
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	1 2 3 4
MEASURE UNDER STEERING BLOCK	MEASURE UNDER REAR UPRIGHT
0	8
DOWNSTOP /mm	

FRONT	TOE /deg.	REAR
OUT 1	TOE IN 2	
BUMPER WINDOW CUT <input type="checkbox"/> NO-CUT <input checked="" type="checkbox"/>	UPPER ARM POSITION 0 1 2 3 4 <input checked="" type="checkbox"/>	FLEX SETTING FIXED <input checked="" type="checkbox"/> FLEX <input type="checkbox"/>
SERVO SAVER	4 3 2 1	

FRONT	REAR
CAMBER /deg. LEFT -1.5 RIGHT -1.5	CAMBER /deg. LEFT -3.0 RIGHT -3.0
ROLL CENTER	ROLL CENTER
SHIM /mm	SHIM /mm
2	2
CAMBER LINK LOCATION	
251	264
TRACK WIDTH /mm	

CHASSIS WEIGHT BALANCE			
FRONT BALANCE	ENGINE MOUNT	REAR BALANCE	
WEIGHT g	2 MOUNTS BLOCK <input checked="" type="checkbox"/> MONOBLOCK <input type="checkbox"/>	WEIGHT g	
GRAPHITE <input type="checkbox"/>	ALUMINUM <input checked="" type="checkbox"/> BRASS <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>	
NONE <input checked="" type="checkbox"/>		NONE <input checked="" type="checkbox"/>	
BATTERIES HOLDER			
WEIGHT g	GRAPHITE <input type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/>	